

Climax S12V300i: Electric stacker

- Hour meter and battery discharge indicator with lift interrupt
- Handling of 2 pallets at the same time (initial lift)
- Lateral access for easy battery replacement



Characteristics			
1.1	Model designation		S12V300i
1.2	Drive unit		Battery
1.3	Operator type		Walkie
1.4	Load capacity	Q (kg)	1200
1.5	Load center	c (mm)	600
1.6	Load distance	x (mm)	700
1.7	Wheelbase	y (mm)	1275
Weights			
2.1	Service weight (Incl. battery)	kg	1050
2.2	Axle loading, loaden operator/load side	kg	775/1475
2.3	Axle loading, unladen operator/load side	kg	715/335
Wheels, Chassis			
3.1	Tyre type		PU/PU
3.2	Tyre size, operator side (diameter x width)	mm	Ø 230 x 70
3.3	Tyre size, load side (diameter x width)	mm	Ø 85 x 70
3.4	Balance wheels (dimensions)	mm	Ø 130 x 55
3.5	Wheels, number operator/load side (x = drive wheels)		1 x + 1/4
3.6	Tread, operator side	b10 (mm)	538
3.7	Tread, load side	b11 (mm)	370
Dimensions			
4.1	Height, mast lowered	h1 (mm)	1967
4.2	Free lift	h2 (mm)	100
4.3	Initial Lift	h5 (mm)	125
4.4	Lift height	h3 (mm)	3000
4.5	Height, mast extended	h4 (mm)	3406
4.6	Height of tiller arm in operating position, min/max	h14 (mm)	825/1225
4.7	Fork height, lowered	h13 (mm)	85
4.8	Overall length	l1 (mm)	1847
4.9	Length to face of forks	l2 (mm)	697
4.10	Overall width	b1/b2 (mm)	800
4.11	Fork dimensions	s/e/l (mm)	60/190/1150
4.12	Outside fork width	b5 (mm)	560
4.13	Ground clearance	m2 (mm)	30
4.14	Aisle width, 1000 x 1200 pallet crossways	Ast (mm)	2400
4.15	Aisle width, 800 x 1200 pallet lengthways	Ast (mm)	2263
4.16	Outer turning radius	Wa (mm)	1423
Performance			
5.1	Travel speed, loaden/unloaden	km/h	5/5,5
5.2	Lifting speed, loaden/unloaden	m/s	0,127/0,15
5.3	Lowering speed, loaden/unloaden	m/s	0,23/0,22
5.4	Maximum gradeability, loaden/unloaden S2 5 min	%	8/16
5.5	Service brake		Electromagnetic
Drive			
6.1	Drive motor rating S2 60 min	kW	1.1
6.2	Lift motor rating at S3 15%	kW	2.2
6.3	Traction battery voltage/rated capacity	V/Ah	24/210
6.4	Battery weight (with box)	kg	205
6.5	Battery compartment dimensions l/w/h	mm	650/540/200
6.6	Battery type		Traction
Others			
7.1	Type of drive control		AC
7.2	Manufacturer		ZAPI
7.3	Sound level at operator's ear	dB (A)	74

